



Technical Specification

Nortel IP Phone 2001

Standard-level IP Phone delivers highly cost-effective solution to the desktop

The Nortel IP Phone 2001 is a standard level, single-line IP Phone, designed to meet the needs of general usage environments and public areas such as school rooms, main lobbies, hallways and break rooms.

The Nortel IP Phone 2001 delivers an economical entry to Nortel's IP Telephony, without sacrificing audio or feature performance. With support for standards-based Power over Ethernet (PoE), the need to locally power the IP Phone 2001 is avoided, resulting in reduced infrastructure costs. Resiliency is enhanced as centralized battery backup services at the wiring closet can be leveraged, powering the phone in the event of power outages.

The Nortel IP Phone 2001 is fully compatible with most Nortel Communication Servers, delivering both high-quality audio performance and user

experience, taking advantage of an extensive array of business telephony features and capabilities to meet the communication demands of the business.

Key features and benefits include:

- › Single-line entry-level IP Phone with small desktop footprint makes it ideally suited to locations with limited desktop space
- › High-quality 3 line x 24 character LCD delivers enhanced user experience with an easy-to-read display
- › Fixed keys include Line, Goodbye, Hold, Volume Bar, Services and Messaging along with up and down navigation arrows
- › Four context-sensitive soft-label keys provide intuitive interface for fast access to menus and system features
- › Integrated high-quality audio speaker supports "Listen Mode" for on-hook dialing support

- › Visual Ringing Alerter/Message Waiting LED
- › Supports 802.3af standards-based PoE and local AC power via power adapter
- › Dynamic IP addressing with a standard DHCP server offers a flexible, simplified solution for handling adds, moves and changes, reducing management costs
- › Secured communications with standards-based user authentication, signaling and media-path encryption
- › Tight linkage with Nortel Communication Servers offers rich suite of reliable, quality-based telephony communications features
- › Added convenience and time savings with field-upgradable firmware using Trivial File Transfer Protocol (TFTP) or for sites requiring enhanced secure firmware upgrades, UNIStim File Transfer Protocol (UFTP)¹

¹ UNIStim File Transfer Protocol (UFTP) is Nortel Communication Server dependent.



Nortel IP Phone 2001



Technical specifications

Platform support

- Nortel Communication Server 1000, 2000 and 2100
- Meridian 1²
- Business Communications Manager (BCM) 50/200/400
- Media Gateway 1000B Expansion Chassis
- Survivable Remote Gateway (SRG)/50/200/400

Phone features

- Four context-sensitive soft label keys
- 3 line x 24 character LCD display
- Seven fixed keys including Volume Bar (Up/Down), Line, Goodbye, Hold, Messages, Services
- Up and down navigation arrows for content as presented on LCD display
- Integrated high-quality audio "Listen Mode" Speaker for on-hook dialing support
- Text and Icon keycap models for global deployments
- Desk and wall mount options

User selectable ring tones

IP Call Recording

- Supports dual media stream IP Call Recording with Nortel Contact Recording and Quality Monitoring (CRQM)

Color

- Charcoal with silver-metallic bezel finish

Dimensions and weight

- Dimensions (WxDxH): 7.48 in x 6.49 in x 6.61 in/190mm x 165mm x 168mm on footstand
- Weight: 1.72lbs/.78g

Power

- Supports IEEE 802.3af Power over Ethernet, Nortel and selected third-party pre-standard³
- AC power: Localized power adapter delivering 48V DC @ 520mA
- Power dissipation: 3.2 watts idle, 4.2 maximum – IEEE Power Class 2

Administration and Security

- 802.1x and Extensible Authentication Protocol (EAP-MD5) for authentication
- Static, Partial and Full Dynamic Host Control Protocol (DHCP) address assignment (Full DHCP factory default)
- Signaling encryption with support for the 128-bit Advanced Encryption Standard (AES)⁴
- 802.1ab Link Layer Discovery Protocol (LLDP) for network discovery and inventory management
- RFC 3711 compliant Secure Real-Time Protocol (sRTP) Pre-shared Key and Public Key Infrastructure (PKI)⁵

Protocols

- Call Control Protocol: UNIStim subset over UDP with reliability layer
- E.164 dialing support

Audio Quality of Service

- G.711 a-law and μ -law, G.723.1 and G.729a and Annex B
- 802.1p/Q, DiffServ
- Supports echo cancellation and silence suppression

Operating temperature

- +5°C to 40°C/40°F to 104°F

Relative humidity

- 5% to 95% (non-condensing)

Storage temperature

- -40°C to 70°C/-40°F to 158°F

EMC

- United States: FCC CRF 47 Part 15 Class B
- Canada: ICES-003, Class B
- Australia/New Zealand: AS/NZS 3548, Class B – CISPR 22
- European community:
 - EN55022, Class B:1998+A1+A2
 - EN 55024:A1+A2
- EN 61000-3-2
- EN 61000-3-3
- Japan:VCCI
- Korea MIC
- China CCC

Safety

- United States: UL 60950-1
- Canada: CSA No. 60950-1-03
- IEC 60950-1
- Australia/New Zealand: AS/NZS 60950.1:2003
- European Community: EN 60950-1 +A11
- Mexico NOM approvals

Other

- FCC Part 68 HAC
- IC CS-03 HAC
- Australia AS/ACIF 004
- New Zealand PTC 220
- Compliant with the essential requirements and other relevant provisions of Directive 1999/5/EC
- Complies with Reduction of Hazardous Substances (RoHS) – (6 of 6) as part of European Union Environmental Directive
- American Disabilities Act (ADA) compliant dialpad

² Requires Signaling Server or Voice Gateway Media Card for support

³ Third-party pre-standard switch support includes Cisco 4503 CATOS 7.6(3), 6503 CATOS 8.3(2), 3550 IOS 12.1(13).

⁴ Requires Secure Multimedia Controller 2450 (SMC 2450) for support on Communication Server 1000 and Multimedia Communication Server 5100.

⁵ Public Key Infrastructure (PKI) is Nortel Communication Server dependent

Nortel is a recognized leader in delivering communications capabilities that make the promise of Business Made Simple a reality for our customers. Our next-generation technologies, for both service provider and enterprise networks, support multimedia and business-critical applications. Nortel's technologies are designed to help eliminate today's barriers to efficiency, speed and performance by simplifying networks and connecting people to the information they need, when they need it. Nortel does business in more than 150 countries around the world. For more information, visit Nortel on the Web at www.nortel.com. For the latest Nortel news, visit www.nortel.com/news.

For more information, contact your Nortel representative, or call 1-800-4 NORTEL or 1-800-466-7835 from anywhere in North America.

Nortel, the Nortel logo, Nortel Business Made Simple and the Globemark are trademarks of Nortel Networks. All other trademarks are the property of their owners.

Copyright © 2007 Nortel Networks. All rights reserved. Information in this document is subject to change without notice. Nortel assumes no responsibility for any errors that may appear in this document.

NN116060-102207

In the United States:

Nortel
35 Davis Drive
Research Triangle Park, NC 27709 USA

In Canada:

Nortel
195 The West Mall
Toronto, Ontario M9C 5K1 Canada

In Caribbean and Latin America:

Nortel
1500 Concorde Terrace
Sunrise, FL 33323 USA

In Europe:

Nortel
Maidenhead Office Park, Westacott Way
Maidenhead Berkshire SL6 3QH UK
Phone: 00 800 8008 9009

In Asia:

Nortel
United Square
101 Thomson Road
Singapore 307591
Phone: (65) 6287 2877



BUSINESS MADE SIMPLE